



# Gas detection just got personal



## PS200 Series

Part of the Personal Surveyor range



Colored 'rubber boot' for multi-site or multi-application working (7 colors available)

- Simple 1-button operation
- Any combination of (LEL/O<sub>2</sub>/CO/H<sub>2</sub>S)
- Audible, visual and vibrating alarms
- Fully certified
- Internal pump (optional)
- Lightweight
- Sensor integrity checking
- Robust construction
- Ease of maintenance

### Auto Bump & Calibration Station

- Simple user interface
- Full bump, calibration and charging options
- Bump/calibration results storage
- Stand-alone, PC or ethernet options
- Robust construction

### Detection, Protection, Innovation



**GMI. CONFIDENCE WHERE SAFETY IS CRITICAL.** Gas Measurement Instruments designs, manufactures and markets a wide range of the highest quality proven personal portable and fixed gas monitoring systems. GMI is an international brand with a worldwide network of distributors and dedicated service centers ensuring fast and effective turnaround on instrument calibration and repair. Our uncompromising engineering excellence, established in over half a century of leadership, enables us to meet the exacting demands of industries where safety is critical. By building and maintaining strong relationships with our customers, GMI understands the unique challenges of the diverse markets we serve. Today, our proud heritage of pioneering gas leak monitors and detectors is shaping the future of GMI.



# PS200 Series

The PS200 Series detects all possible combinations of LEL, O<sub>2</sub>, CO, H<sub>2</sub>S, including single gas detection. In addition to displaying all gas readings simultaneously, the user can also initiate a manual bump test anytime.

The PS200 accessory pack includes the following as standard: USB Charging/Comms Clip, Universal Power Plug, User CD-ROM, Quick Operating Instructions. Tubing (3m) complete with a Quick Connector is also supplied as standard with pumped instruments.

## Features




TECHNICAL SPECIFICATION	
<b>Size:</b>	121 x 59 x 32mm (4.8" x 2.3" x 1.3")
<b>Weight:</b>	230g (8oz) with pump 215g (7.6oz) without pump
<b>Temperature:</b>	-20°C to +50°C (-4°F to 122°F)
<b>Humidity:</b>	0 to 95% R.H non-condensing
<b>Alarms:</b>	Highly visible flashing LED, piercing >90dB audible
<b>Display:</b>	Green and red LCD backlight display
<b>Datalogging:</b>	Timed: 24 hours of timed logs at 1 log per minute Session: Minimum of 180 logs Calibration: Minimum of 8 calibration logs Bump Logs: Minimum of 180 logs
<b>Battery:</b>	Lithium Ion rechargeable battery Run Time: Up to 14 hrs (diffusion) Charging Time < 4 hrs
<b>Enclosure:</b>	High impact rubberized polycarbonate case
<b>Drop Test:</b>	3m (10ft)
<b>IP Rating:</b>	IP67 (Dust-tight and waterproof to 1m)
<b>Response Times (T<sub>90</sub>):</b>	LEL = 10 secs (IEC 60079-29-1) O <sub>2</sub> = 12 secs (BSEN 50 104) CO < 20 secs H <sub>2</sub> S < 20 secs
<b>Approvals:</b>	IEC Ex ia d IIC T4 Gb ATEX Ex II 2 G Ex ia d IIC T4 (Ex) CSA Class 1 Div 1 Groups A,B,C,D, T4 Class 1, Zone 1 EX ia d IIC T4 MED (0038/YY) - Module B & E CE 0518
<b>Warranty:</b>	2 years as standard



Red display in alarm conditions



Configurable calibration options



Configurable bump options

# Automatic Bump Testing and Calibration

To complement the Personal Surveyor product line, GMI has developed a compact, robust and easy to use Auto Bump & Calibration Station that can provide full bump and calibration options. Data transfer is facilitated using a USB memory stick with Standalone software that is simple to set up and customize based on end users' specifications. Standalone, PC, and ethernet versions are available.



## Standalone

By adding the Auto Bump & Calibration Station to your PS200 package, data can be easily retrieved using specific software in a user-friendly time logged format. This gives you the ability to create and print your personalized calibration certificate.

## PC

Allows easy configuration (bump test or calibration) of Auto Bump & Calibration Station and allows all results to be automatically stored to a database on the PC. The stored results can be easily viewed and calibration certificates produced. The history of all results can be easily viewed and reports of instruments can be easily compiled.

## Ethernet


Same as PC except multiple units can be connected to a network allowing one PC to control and receive data.

### AUTO BUMP & CALIBRATION STATION TECHNICAL SPECIFICATION

<b>Size:</b>	200 x 140 x 135mm (7.9" x 5.5" x 5.3")
<b>Weight:</b>	1.2kg (43oz)
<b>Interfaces:</b>	Standalone /USB /Ethernet
<b>LED Indicators:</b>	Power (Green) /Testing (Yellow) /Pass (Green) / Fail (Red)
<b>Testing Time:</b>	Bump Test 60 secs Calibration Test 90 secs
<b>Data Storage:</b>	>6000 Bump & Calibration results
<b>Power Supply:</b>	12V dc, 2A
<b>Operating Temperature:</b>	-10°C to 40°C (14°F to 104°F)
<b>Gas Ports:</b>	3 (Air, Combi Gas & Exhaust) Contact GMI for other combinations

### SENSOR SPECIFICATIONS

GAS	RANGES	INCREMENTS	SENSOR TYPE
LEL	0-100% LEL	1% LEL	Catalytic Bead
O <sub>2</sub>	0-25%	0.1%	Electrochemical
CO	0-1000ppm	1ppm	Electrochemical
H <sub>2</sub> S	0-100ppm	1ppm	Electrochemical



### ORDERING INFORMATION AND ACCESSORIES

Accessories supplied with the instrument	
64260	USB Charging / Comms Clip
64247	Universal Power Plug (Mains – USB)
64190	User CD-ROM (Incl. Handbook)
64172	Quick Operating Instructions
64136	3m. Tubing with Quick Connector

### RECOMMENDED SPARE PARTS

64254	Hydrophobic Filter
64084	Sample Inlet Filter
64825C	LEL sensor
64066	O <sub>2</sub> sensor
64067	Dual Toxic CO/H <sub>2</sub> S Sensor
64176	CO sensor
64128	H <sub>2</sub> S sensor
64255	Pump Assembly

### ADDITIONAL ACCESSORIES

64303	Rubber Boot (Color options:- black, grey, yellow, red, orange, blue, green)
66123	Hand Aspirator
66478	Hand Aspirator (c/w 10 ft. tubing)
66112	Sample Line Extender
66485	In-Line Hydrophobic Filter Assy
66545	Ball Float
64100	Rugged Carry Case
Charging Accessories	
64248	In-Vehicle Charging Adaptor (12V/24V – USB)
64138	5 Way Multi-Charger
Automatic Bump & Calibration	
64052	Auto Bump & Calibration Station (6mm. fittings & incl. PSU and USB stick with Standalone software)
64052Q	Auto Bump & Calibration Station (1/4 in. fittings & incl. PSU and USB stick with Standalone software)
99553	flexiCal Plus software for PC
99118	Demand Flow Regulator
64265	Tubing with 6mm Push Fit Connector
Manual Bump & Field Calibration Kit	
64051	Manual Bump Kit (no power required) (c/w Combi Test Gas 99146, Direct Flow Regulator, tubing & sample line connector)
Gas Kits for Auto Bump & Calibration Station	
99146	Combi Test Gas Cylinder (2.5% CH <sub>4</sub> , 500ppm CO, 50ppm H <sub>2</sub> S, 18% O <sub>2</sub> , balance N <sub>2</sub> )
64060	Test Gas Kit (6mm fittings) (Combi Test Gas 99146, Demand Flow Regulator 99118 c/w 6mm tubing)
64060Q	Test Gas Kit (1/4 in Fittings) (Combi Test Gas 99146, Demand Flow Regulator part no. 99118 c/w 1/4" tubing)
Software	
64197	Data downloading CD-ROM (c/w Handbook)
64184	Auto Bump & Calibration Station USB Flash Drive (c/w Handbook)
Documentation	
64193	Configuration & Field Calibration Handbook (CD-ROM)

#### Distributed by: