External Pump

Allows Gas Clip diffusion detectors to take remote samples from up to 75 feet away



- Compatible with all GCT multi gas and single gas diffusion detectors
- Draws samples at 2 ft. per second (using 1/8" id tubing)
- 52-hour continuous run time
- Rechargeable battery (charger included)
- 4 to 6-hour recharge time (typically)
- Users can perform manual block tests
- Audio & visual alerts for blockages and low battery
- IP 68 rating to withstand the harshest environment



Portable Gas Detectors You Can Count On

gascliptech.com • +1.972.775.7577 • Toll-free: 1.877.525.0808 email: info@gascliptech.com



OTHER INCLUDED ITEMS

Charger, Ten-foot Hose, Three-foot Hose, Stainless Steel Diffusion Stone, 10 Additional Filters (5 Hydrophobic & 5 Particulate) & Quick Start Guide

COMPATIBLE ACCESSORIES



6ft. Telescoping Sampling ProbePart# MGC-TSPROBE



MGC Remote Sampling Probe
Part# MGC-PROBE-1



MGC Pump Quick Disconnect*
Part# MGC-PUMP-QD



MGC Multi Charger Part# MGC-CHRG-MULTI





Hose By The Foot Part# HOSE-FT



Confined Space Kit
Part# CSK-XP
XP Included



Confined Space Kit w/ Gas
Part# CSK-XP-GAS
XP Included

SPECIFICATIONS

Part Number GCT-XP

Size • Weight 6.4" H x 2.6" W x 1.25" D (163 x 68 x 31 mm) • 8 oz (235g)

Temperature -7.6° to +122°F (-22° to +50°C)

Humidity 5% to 100% RH (non-condensing)

Battery Life 52 hours (continuous)

Charge Time 4 - 6 hours (typically)

Alarms Visual & audible (minimum 95 dB)

LED's Flow Light--indicates that pump is on and/or blocked

Power Light--indicates that the pump is on and the amount of

battery life remaining

Battery Light--indicates when the pump is charging and when

it is fully charged

Tests Full-function self test upon activation

Battery test runs continuously

Ratings IP 68

Gas Inlet 1/8" Stainless steel barbed fitting

Pump Draw Sample from up to 75 ft. (23 m)

Certifications and Approvals



CSA: C22.2 152, ISA S12.13.01 Class I, Division 1, Group A, B, C, and D, T4 Class I, Zone 0, AEx ia IIC T4 Ga -20°C ≤ Tamb ≤+50°C



IECEx: IECEx CSA 21.0006X Ex ia IIC T4 Ga -20° C \leq Tamb \leq $+50^{\circ}$ C

ATEX: CSANe 21ATEX2143X EX II 1 G Ex ia IIC T4 Ga -20°C ≤Tamb ≤+50°C; 4.2Vdc

Warranty Full 2 years

Specifications are subject to change without notice due to ongoing product development.

Distributed by:

